

RNAV (GPS) RWY 20R

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Soldatna altimeter setting. Circling Rwy 2R, 20L NA at night. When local altimeter setting not received, use Soldatna altimeter setting and increase all DA 22 feet and all MDA 40 feet, increase LNAV visibility Cat C and D to RVR 5000. Circling Rwy 2W, 20W NA. # RVR 1800 authorized with use of FD or AP or HUD to DA. (NA when using Soldatna altimeter setting).



MISSED APPROACH:
Climb to 2000 direct
FOPTY and hold.

YILUS (IAF)

2000 NoPT (9.2)

5 NM

016°

196°

2000 NoPT (8.9)

263°

ZUTOR (IAF)

(IF/IAF) TBONE

1400 (6.4)

96°

2000 to TBONE 016° (8)

KENAI

ENA

252

RW20R

3500

MSA RW20R 25 NM

MISSED APCH FIX

5 NM

196°

016°

FOPTY

ELEV 100	D	TDZE 98
----------	---	---------

196°

ELEV 100

D TDZE 98

196°

20W

20R

20L

20R

4600 x 240

7855 x 150

1980 x 75

TWIR

☆

REIL Rwy 2L

HIRL Rwy 2L-20R

AK, 19 MAR 2026 to 14 MAY 2026