RNAV 1 - DME/DME/IRU or GPS.
RADAR required.
TOP ALTITUDE:
RWYS 31L/R: 5000
RWYS 17C/R, 18L/R,
35L/C, 36L/R: 10000
LONE STAR DEP CON
118.55 290.35
D-ATIS DEP
135.925
CLNC DEL
128.25
CPDLC
GND CON
121.65 121.8 (EAST)
121.85 (WEST)
DFW TOWER
126.55 127.5 (EAST)
124.15 134.9 (WEST)
NOTE: For use by turbojet aircraft only.
NOTE: Non-RNAV capable props: file and expect DALLAS or GARLAND DEPARTURE.
NOTE: RNAV capable props: file and expect the KUSSO RNAV DEPARTURE.
CUZEN
5000
FEZTR
7000
SWYFT
ZERLU
TRRCH
CORTS
JGIRL
5000
SPERA
JAYXX
SWDIA
ZACHH
TRYTN
FORCK
LOOSE
LYING
JJANE
MRSSH
HANUH
THHOR
082° (4)
095° (6)
108° (27)
090° (27)
084° (5)
107° (3)
090° (27)
095° (18)
090° (12)
1000
*2000
*2100
*2400
990 (27)
1120
356°
004°
090°
176°
157°
155°
145°
143°
N
TAKEOFF MINIMUMS
Rwys 31L/R: Standard.
Rwys 17C/R, 18L/R, 35L/C, 36L/R: Standard
with minimum climb of 500' per NM to 1120.
(CONTINUED ON FOLLOWING PAGE)
NOTE: Chart not to scale.