

LOC/DME I-SZI 111.7 Chan 54	APP CRS 164°	Rwy Ldg 9426 11901 TDZE 430 432 Apt Elev 432 432
---	------------------------	--

ILS or LOC RWY 16C

SEATTLE-TACOMA INTL (SEA)








DME or RADAR required. From GRIFY: RNAV 1-GPS required.

▼ Inop table does not apply to Sidstep 16L Cats A/B. Simultaneous approach authorized with Rwy 16R. Simultaneous operations require use of vertical guidance, maintain last assigned altitude until established on glideslope. For inop ALS, increase S-LOC 16C Cat C, D visibility to RVR 5500. See additional requirements on adjacent information page.

ALSF-2 Rwy 16C/L

MISSED APPROACH: Climb on heading 160° and SEA VORTAC R-161 to cross TEBNE/SEA 2.4 DME/RADAR at or below 2000, then climb to 5000 on SEA VORTAC R-161 to MILLT/SEA 11 DME/RADAR and hold, continue climb-in-hold to 5000.

D-ATIS 118.0	SEATTLE APP CON 133.65 273.45	SEATTLE TOWER 119.9 239.3 (16L, 16C, 34C, 34R) 120.95 239.3 (16R, 34L)	GND CON 121.7
------------------------	---	--	-------------------------



CATEGORY	A	B	C	D
S-ILS 16C	630/18		200 (200-½)	
S-LOC 16C	800/24	370 (400-½)	800/35	370 (400-¾)
SIDESTEP 16L	800/55 368 (400-1)		800-1½ 368 (400-1½)	
CIRCLING	1000-1	568 (600-1)	1000-1½ 568 (600-1½)	1000-2 568 (600-2)

