ILS RWY 2L (SA CAT I)

NASHVILLE INTL (BNA)

LOC/DME I-BNA	APP CRS	Rwy Ldg	7702
109.9	021°	TDZE	599
Chan 36		Apt Elev	599

DME or RADAR required. RADAR required for procedure entry.

Simultaneous approach authorized. Requires specific OPSPEC, MSPEC, or LOA approval.

ALSF-2

MISSED APPROACH: Climb to 1200 then climbing left turn to 4000 on heading 240° and on BNA VORTAC R-270 to BEVEE/BNA VORTAC 22.4 DME/RADAR and hold.

D-ATIS	NASHVILLE APP CON	NASHVILLE TOWER	GND CON
135.1	118.4 360.7 (030°-196°) 119.35 372.0 (197°-029°)	118.6 257.8	121.9 348.6

MISSED APCH FIX
BEVEE
BNA 22.4
RADAR
090°
270°
114.1 BNA
R-270
Chan 88

R-270

NASHVILLE
114.1 BNA
Chan 88

LOCALIZER 109.9
I-BNA
Chan 36

IM
730

2500
021° (2.5)

DOBBS
I-BNA 7.2
RADAR

DIKNS
I-BNA 9.7
RADAR

(IF)
FIDDS
I-BNA 13
RADAR

3000
021°
(3.3)

4000
021°
(3.8)

CRRAG
I-BNA 16.8
RADAR

5000
021°
(4.8)

HOLD 6000

(IAF)
DIFFE
BNA 21.3
RADAR

199°
1 min
019°

BNA
R-199

201°

MSA BNA 25 NM
3100

ELEV 599 D TDZE 599





1200	4000 hdg 240°	BNA R-270	BEVEE △

Use I-BNA DME when on the LOC course.

CATEGORY	A	B	C	D
S-ILS 2L	RA 155/14 150 DA 749			

SA CATEGORY I ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

HIRL all Rwys
TDZL/RCLS Rwys 2L and 2R
REIL Rwys 13, 20C and 31

SE-1, 11 JUN 2026 to 09 JUL 2026
SE-1, 11 JUN 2026 to 09 JUL 2026