


WAAS CH 69499 W12A	APP CRS 123°	Rwy Ldg TDZE 541 Apt Elev 617	8956
--	------------------------	---	-------------

RNAV (GPS) Y RWY 12L


ST LOUIS LAMBERT INTL (STL)

RNP APCH - GPS.		ALSF-2 	MISSED APPROACH: Climb to 3000 direct ODITY and on track 071° to TOY VORTAC and hold.
RADAR required for procedure entry.			
<p>▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Simultaneous approach authorized with Rwy 11. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LPV all Cats visibility to RVR 6000, LNAV/VNAV all Cats visibility to 1½ SM, and LNAV Cat C/D/E visibility to 1½ SM.</p>			

D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 120.05 284.6	GND CON 121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	CLNC DEL 119.5 363.1	CPDLC
--	---	--	---	--------------------------------	-------



ELEV 617	D	TDZE 541
----------	----------	----------



RUYON		EUBIE		GREP		ODITY		TOY	
5000		4000		2500		3000		tr 071°	
GP 3.00°		TCH 54		1.4 NM to RWY 12L					
5.6 NM		7.4 NM		4.5 NM		1.4 NM			
CATEGORY	A	B	C	D	E				
LPV DA	951/50		410 (400-1)						
LNAV/VNAV DA	1040/60		499 (500-1¼)						
LNAV MDA	1040/24		499 (500-½)		1040/50		499 (500-1)		1040/60
									499 (500-1¼)