

|  |                        |   |
|--|------------------------|---|
| WAAS<br>CH <b>58299</b><br><b>W01A</b> | APP CRS<br><b>006°</b> | Rwy Ldg <b>6300</b><br>TDZE <b>6431</b><br>Apt Elev <b>6451</b> |
|--|------------------------|---|

# RNAV (GPS) X RWY 1

## JACKSON HOLE (JAC)

|  |            |   |
|--|------------|---|
| RNP APCH-GPS.  | MALS<br>A2 | MISSED APPROACH: Climb to 14000 direct QUIRT and on track 088° to DNW VOR/DME and hold, continue climb-in-hold to 14000.<br>*Missed approach requires minimum climb of 385 feet per NM to 7700. |
| <p>▼ Circling NA east of Rwy 1-19. Baro-VNAV NA.</p> <p>▲ Circling NA for Cat D. Inop table does not apply to LPV, LPV*, LNAV/VNAV, and LNAV Cat C/D.</p> <p>☁ -21°C</p> |            |   |

|                          |   |  |                          |                         |
|--------------------------|---|--|--------------------------|-------------------------|
| D-ATIS<br><b>120.625</b> | SALT LAKE CENTER<br><b>133.25 285.6</b> | JACKSON TOWER*<br><b>118.075</b> (CTAF) <b>1</b> | GND CON<br><b>124.55</b> | UNICOM<br><b>122.95</b> |
|--------------------------|---|--|--------------------------|-------------------------|



|                      |                           |              |                           |          |                         |          |    |          |  |          |  |          |  |
|----------------------|---------------------------|--------------|---------------------------|----------|-------------------------|----------|----|----------|--|----------|--|----------|--|
| 7 NM Holding Pattern |                           | VALCU        |                           | DECEV    |                         | ZUGEN    |    | COVGI    |  | QUIRT    |  | DNW      |  |
| 17500 ← 186°         |                           | 11700 → 006° |                           | 11000    |                         | 10400    |    | 9500     |  | 8180     |  | 14000    |  |
| GP 3.00°             |                           | TCH 50       |                           |          |                         |          |    |          |  | Ir 088°  |  | DNW      |  |
|                      |                           | ← 4.3 NM     |                           | ← 3.7 NM |                         | ← 5.5 NM |    | ← 4.1 NM |  | ← 2.1 NM |  | ← 3.4 NM |  |
| CATEGORY             | A                         |              | B                         |          | C                       |          | D  |          |  |          |  |          |  |
| LPV DA*              |                           |              | 6651/40                   |          | 220 (200-¾)             |          |    |          |  |          |  |          |  |
| LPV DA               |                           |              | 7445-4                    |          | 1014 (1000-4)           |          |    |          |  |          |  |          |  |
| LNAV/VNAV DA         |                           |              | 7327-4                    |          | 896 (900-4)             |          |    |          |  |          |  |          |  |
| LNAV MDA             | 7540/55<br>1109 (1100-1)  |              | 7540-1½<br>1109 (1100-1½) |          | 7540-3<br>1109 (1100-3) |          |    |          |  |          |  |          |  |
| CIRCLING             | 7540-1½<br>1089 (1100-1½) |              | 7540-1½<br>1089 (1100-1½) |          | 7560-3<br>1109 (1200-3) |          | NA |          |  |          |  |          |  |