

RNAV (GPS) RWY 2L

KENAI MUNI (ENA) (PAEN)

⚠ Baro-VNAV NA when using Soldotna altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). When local altimeter setting not received, use Soldotna altimeter setting: increase LPV DA to 366 feet and LNAV/VNAV DA to 429 feet and all MDA 40 feet; increase LPV and LNAV/VNAV visibility all Cats and LNAV Cat C/D visibility ½ mile; increase Circling Cat D visibility ¼ mile. VDP NA when using Soldotna altimeter setting. Circling RWY 2R, 20L NA at night. Circling RWY 2W, 20W NA.

MISSED APPROACH:
Climb to 2000 direct
TBONE and hold.

KENAI RADIO
122.65

2000 to FOPTY
196° (14.6)



2000 NoPT
087°
(9.7)

5 NM.

016
(6.1)

2000 NoPT
3130

(IAF)
KASSI

MSA RW02L 25 NM

3500

5 NM
Holding Pattern

FOPTY

CAPRU

2000

* LNAV only

2000 -
GP 3.00°
TCH 53

-0148

*1.1 NM to
RW021

W02L

[illegible]

184

38 NIA

CATEGORY	A	B	C	D
LPV DA	344-¾ 250 (300-¾)			
LNAV/VNAV DA	407-1 313 (400-1)			
LNAV MDA	480-1 386 (400-1)		480-1½ 386 (400-1½)	
CIRCLING	560-1 460 (500-1)	580-1 480 (500-1)	580-1½ 480 (500-1½)	740-2 640 (700-2)

ELEV 100	D	TDZE 94
----------	----------	---------

D

TDZE 94

REIL Rwy 2L **L**
HIRL Rwy 2L-20