

KING SALMON, ALASKA

HI-ILS Z or LOC Z RWY 12

LOC/DME I-AKN

110.3

Chan 40

APCH CRS

121°

Rwy Idg

8501

TDZE

62

Arpt Elev

73

[USAF]

KING SALMON (AKN) (PAKN)

DME required. RADAR required for procedure entry.

MALSR

A5

MISSED APPROACH: Climb to 600, then climbing right turn to 3000 via heading 240° and AKN VORTAC R-210 to OLLER/AKN 15 DME and hold.

ATIS

128.8

ANCHORAGE CENTER

124.8 354.0

TOWER

118.3 279.5

GND CON

121.9

CTAF

121.90 352.05

UNICOM

122.95

† When control tower closed, increase RVR to 50.
Autopilot coupled approaches not authorized below 700' MSL.

NOVET RADAR

30

FL2000

116°

2000

1700

121°

Intcp Lczt NIRRI I-AKN 15.3

KINGE I-AKN 6.6

ZOPUB I-AKN 3

AKN VORTAC

560

I-AKN 1.6

GS 3.00°

TCH 66

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp AKN R-210

OLLER AKN 15

Use I-AKN DME when on localizer course

172

121°

81

70±

4017 ± 100

8900 ± 150

100±

36

TWR

3

A5

P

P

CATEGORY	C	D	E
S-ILS 12*†	262/24	200 (300-½)	
S-LOC 12**†	420/30	358 (400-¾)	
CIRCLING	580-1½ 507 (600-1½)	900-2¾ 827 (900-2¾)	960-3 887 (900-3)

KING SALMON, ALASKA

58°41'N-156°39'W

KING SALMON (AKN) (PAKN)

Amtd 8 22APR21

HI-ILS Z or LOC Z RWY 12