

LOC I-PBV 110.1	APP CRS 111°	Rwy Ldg TDZE Apt Elev	4982 128 128
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 11

ST GEORGE (PBV) (PAPB)

⚠

DME from SRI NDB/DME. Simultaneous reception of I-PBV and SRI DME required. Circling NA north of Rwy 11-29. ADF and DME required. Inop table does not apply to S-LOC 11 Cats A and B and S-ILS 11 all Cats.

MALSF

MISSED APPROACH: Climb to 3200 on SRI NDB/DME bearing 110° to LIJFY/SRI 7.7 DME and hold, continue climb-in-hold to 3200.

ASOS 135.45	ANCHORAGE CENTER 119.1 339.8	CTAF 122.8
-----------------------	--	----------------------

IAF ST PAUL ISLAND
314 SPY
DME Chan 36 (109.9)

3000 (130.7)
153°
291°
298°
2100 111° (6)
066°
246°
3000 to APOTE 292° (6.1)
635
677
WIVOG SRI [3.3]
PRIIBLOF 399 SRI
DME Chan 96 (114.9)
LOCALIZER 110.1
I-PBV
LIJFY SRI [7.7]
3200 290° (7.7)
110°
110°
290°
314 SPY
DME Chan 36 (109.9)
LIJFY SPY 46.6
136°
316°

MSA SRI 25 NM
2100

ELEV 128	TDZE 128
----------	----------

111°
4982 X 1.50
29°

REIL Rwy 29
HIRL Rwy 11-29

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

ADF and DME REQUIRED				
CATEGORY	A	B	C	D
S-ILS 11	428-1 300 (300-1)			NA
S-LOC 11	840-1	712 (800-1)	840-1 3/4 712 (800-1 3/4)	NA
CIRCLING	840-1 712 (800-1)	980-1 1/4 852 (900-1 1/4)	980-2 1/2 852 (900-2 1/2)	NA

ST GEORGE, ALASKA
Amdt 1 13SEP18

56°35'N-169°40'W

ST GEORGE (PBV) (PAPB)
ILS or LOC RWY 11