

RNAV (GPS) RWY 24

GEORGE DOWNER (AIV)


APP CRS	Rwy Ldg	5001
244°	TDZE	150
	Apt Elev	150

RNP APCH - GPS


NA Rwy 24 helicopter visibility reduction below 1 SM NA. Procedure NA at night.
Use TCL altimeter setting; when not received, use GTR altimeter setting and increase all MDAs 20 feet, and LNAV visibility Cat C/D 1/2 SM, and Circling visibility Cat C 1/2 SM.

MISSED APPROACH:
Climb to 3000 direct
ZESLO and hold.

TCL ASOS 132.825	COLUMBUS APP CON 135.6 323.275	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



ELEV 150	TDZE 150
----------	----------



Visual Segment - Obstacles.	ZESLO	ZOLUG	CIKOB	4 NM Holding Pattern
	3000	2000	3000	6000
	FEPON 2.8 NM to RW24			
	1100	2000		
	2.8 NM	2.8 NM	6.4 NM	
CATEGORY	A	B	C	D
LNAV MDA	820-1	670 (700-1)	820-1 ⁷ / ₈	670 (700-1 ⁷ / ₈)
CIRCLING	820-1	670 (700-1)	820-1 ⁷ / ₈	940-2 ³ / ₄ 670 (700-1 ⁷ / ₈) 790 (800-2 ³ / ₄)

SE-4, 11 JUN 2026 to 09 JUL 2026

SE-4, 11 JUN 2026 to 09 JUL 2026