


WAAS CH 56204 W06A	APP CRS 058°	Rwy Ldg TDZE 773 Apt Elev 799
--	------------------------	---


RNAV (GPS) Y RWY 6L
CLEVELAND-HOPKINS INTL (CLE)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). Circling Rwy 10 NA at night. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5500 and increase LNAV Cats C/D visibility to 1½ SM.	ALSF-2 A	MISSED APPROACH: Climb to 3000 direct ACAPO and on track 001° to PASLE and hold.
---	-------------	--

D-ATIS 127.85	CLEVELAND APP CON 126.55 346.325	CLEVELAND TOWER 124.5 273.45	GND CON 121.7 273.45
-------------------------	--	--	--------------------------------



ELEV 799		D		TDZE 773	
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).					
BETLL		DEVYL		ACAP0	
2900		2300		3000	
GP 3.00°		058°		tr 001°	
TCH 55		2000		PASLE	
1.9 NM		1.1 NM		2.4 NM	
1.3 NM		1.3 NM		*LNAV only.	
CATEGORY A		B		C	
LPV DA		973/18		200 (200-½)	
LNAV/VNAV DA		1120/30		347 (400-⅝)	
LNAV MDA		1260/24 487 (500-½)		1260/50 487 (500-1)	
CIRCLING		1420-1 621 (700-1)		1420-2 621 (700-2)	



EC-2, 09 JUL 2026 to 06 AUG 2026

EC-2, 09 JUL 2026 to 06 AUG 2026