FORT SILL, OKLAHOMA

RNAV (GPS) RWY 18

HENRY POST AAF (KFSI)

APCH CRS	Rwy ldg	5002
176°	TDZE	1188
	Arpt Elev	1188

- (USA)

RNP APCH

MISSED APPROACH: Climb to 3500 direct to FESAD and hold.

ATIS	FORT SILL APP CON/DEP CON	CLNC DEL	CTAF	ASR
135.425 354.025	120.55 322.4	121.7 279.575	124.95	



Procedure NA for arrivals at NEADS on V77 Northbound.

When local altimeter setting not received, use Lawton-Fort Sill RGNL altimeter setting.

For uncompensated Baro-VNAV systems, Procedure NA below -17°C or above 54°C.

Procedure NA for arrival on HBR VORTAC Airway Radials 354 CW 175.



CATEGORY	A	B	C	D
LNAV/VNAV DA	1673-1⅜ 485 (500-1⅜)			
LNAV MDA	1600-1 412 (500-1)		1600-1⅛ 412 (500-1⅛)	
C CIRCLING	1680-1 492 (500-1)	1760-1 572 (600-1)	1820-1¾ 632 (700-1¾)	1920-2¼ 732 (800-2¼)

SC-1, 09 JUL 2026 to 06 AUG 2026

SC-1, 09 JUL 2026 to 06 AUG 2026