

LOC I-LKS	APP CRS	Rwy Ldg	7250
<u>109.1</u>	297°	TDZE	480
		Apt Elev	501

LOC RWY 29
LOUISVILLE MUHAMMAD ALI INTL (SDF)

	RADAR required. ADF or DME required.
--	--------------------------------------

V Circling Rwy 11 NA at night. Rwy 29 helicopter visibility reduction
A below RVR 4000 NA. For inop ALS, increase S-29 visibility Cats A/B to
RVR 5500 and Cats C/D to 1 $\frac{1}{2}$ SM.

MALSR



MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 heading 268° and on IJU VORTAC R-279 to DAMEN and hold.


D-ATIS
118.725

LOUISVILLE APP CON
132.075 327.0

LOUISVILLE TOWER
124.2 257.8

GND CON
121.7 348.6

MISSED APCH FIX



LOCALIZER 109.1
I-LKS 
LOC offset 1.05°

LOM/IAF
LAANG
414 LK ::::

HOLD $\overline{4900}$
 $\overline{2300}$
2000
2070 16 4

(IAF)

BETHY
IIU 17.8

Procedure NA for arrivals at BETHY on V4 westbound.

LOUISVILLE
14.8 IU ::
Chap 95

4000 NoPT to
TRUBS
252° (1.2) and
297° (4.7)

ELEV 501		TDZE 480
----------	---	----------

