

APP CRS
350°

Rwy Ldg
TDZE
Apt Elev

10000
464
501

RNAV (RNP) Z RWY 35L

LOUISVILLE MUHAMMAD ALI INTL (SDF¹)

RNP AR APCH - GPS.

T

For uncompensated Baro-VNAV systems, procedure NA below -10°C or above 54°C. Simultaneous approach authorized. For inop ALS, increase RNP 0.11 all Cats visibility to RVR 4500.

ALS-F2

A

MISSED APPROACH: Climb to 1000 then climbing left turn to 4000 direct DAMEN and hold.

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6
-------------------	-------------------------------------	---------------------------------	------------------------

MISSED APCH FIX

4 NM

279°

099°

DAMEN

RW35L

350° (5.9)

(FAF) CRDNL

2400 (5.4)

BEEPO 190K

4000 (16)

(IF) DPAUW 6000 210K

350° (3.5)

RDBRD 210K

350° (4.1)

(IAF) BRBON 6000

5300 (4.8)

(IF) AABEY 6000 210K

MUGNZ

2400 (9.3)

3000 (3.1)

(IF) AWLEE 210K

350° (3)

KNNOX

350° (3.1)

3000 (3.1)

(IF) AWLEE 210K

SEE INSET FOR ROUTING TO AWLEE

Procedure NA for arrivals at BRBON on V5-513 southbound.

MSA RW35L 25 NM

3600

ELEV 501

D

TDZE 464

7251 X 150

11887 X 150

35L

35R

TWR

HIRL all Rwys TDZL/RCLS Rwys 17L, 17R, 35L and 35R

R-3704 A & B

1000

4000

DAMEN

△

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).

CRDNL 2400

GP 3.00° TCH 59

See planview for multiple IF locations.

5.9 NM

CATEGORY	A	B	C	D
RNP 0.11 DA	769/24	305 (300-½)		
RNP 0.30 DA	897/40	433 (400-¾)		

AUTHORIZATION REQUIRED

LOUISVILLE, KENTUCKY

Amdt 2 11JUL24

38°10'N-85°44'W

LOUISVILLE MUHAMMAD ALI INTL (SDF¹)

RNAV (RNP) Z RWY 35L