

ILS or LOC Z RWY 1

LOC I-RFB <u>110.1</u>	APCH CRS <u>007°</u>	Rwy Idg TDZE Arprt Elev 9001 580 580	[USAF]	SELFREDGE ANGB (KMTCT)
----------------------------------	--------------------------------	---	--------	------------------------

▼ * When ALS inop, increase RVR to 45, vis to ¾ mile.
 ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile; CAT CDE RVR to 60, vis to 1½ miles.
 *** Circling not authorized W of Rwy 01-19.

ATIS
125.325 270.1

APP CON ★
119.6 391.9

TOWER ★
120.15 (CTAF) 0 225.4

GND CON
128.3 275.8

Visibility reduction by helicopters not authorized.

LOCALIZER 110.1
I-RFB [Symbol]

SELFREDGE
Chan 64 MTC [Symbol]

CUBEN MTC 0.7

LAJOY MTC 5.6

ASAKE MTC 10

SQYRS MTC 12

R-096

HOLD 5000 4000

UNITED STATES CANADA 2700 MTC 10

MSA MTC 2.5 NM 2800

CERUS MTC 10

CAUTION: 5 NM Intermediate Segment Length. Recommend Early Configuration.

EMERG SAFE ALT 100 NM 3100

ELEV	580	TDZE	580
TWR	[Symbol]		
A1	[Symbol]		
P	[Symbol]		
A2	[Symbol]		
P	[Symbol]		
01	[Symbol]		

CATEGORY	A	B	C	D	E
S-ILS 01*	873/40		293	(300-¾)	
S-LOC 01**	1000/40 420 (500-¾)		1000/50		420 (500-1)
CIRCLING ***	1040-1 460 (500-1)	1040-1½ 460 (500-1½)		1140-2	560 (600-2)

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38