

▼

[USN]

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 10: Climbing left turn heading 050°. Thence...

TAKEOFF RWY 28: Climb heading 280°. Thence...

...via RADAR vectors to assigned transition. Maintain 2000 or assigned altitude. Expect clearance to requested altitude/flight level 10 minutes after departure.

ATLIC TRANSITION (NGU3.ATLIC): Via vectors to ATLIC.

ELIZABETH CITY TRANSITION (NGU3.ECG): Via vectors to SWOPE, then via ORF VORTAC R-201 to VISOW (ORF R-201/33 DME), then direct ECG VOR/DME.

FLAT ROCK TRANSITION (NGU3.FAK): Via vectors to WAKS, then via ORF VORTAC R-290 to KELLE, then direct FAK VORTAC.

HARCUM TRANSITION (NGU3.HCM): Via vectors to HCM VORTAC.

HOPEWELL TRANSITION (NGU3.HPW): Via vectors to HPW VORTAC.

J174 TRANSITION (NGU3.ORF): Via vectors to J174.

V139 TRANSITION (NGU3.ORF): Via vectors to V139.

NOTE: Transitions are part of the Preferred Departure Route (PDR) system and established as an Air Traffic flow procedure from the Norfolk Terminal Area. These fixes are to be used as the initial filing point out of NS Norfolk.