


WAAS Ch 49199 W31A	APP CRS 310°	Rwy Ldg 4559 TDZE 390 Apt Elev 390
--	------------------------	---

RNAV (GPS) RWY 31
TEXARKANA RGNL-WEBB FLD (TXK)

RNP APCH-GPS. ▼ Rwy 31 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use De Queen altimeter setting and increase all DA/MDA 100 feet, increase LPV and LNAV/VNAV all Cats, and LNAV Cat C and D visibility ¼ SM, and Circling Cat C and D visibility ¼ SM. Baro-VNAV and VDP NA when using De Queen altimeter setting. ▲	MISSED APPROACH: Climb to 2000 direct JELGA and hold.
---	--

ATIS 120.2	FORT WORTH CENTER 123.925 269.475	TEXARKANA TOWER★ 123.875 (CTAF) 0 235.625	GND CON 119.225
----------------------	---	---	---------------------------






DUBOW Δ 2000
(4.1)

WATLE
(IAF)
ZIROX

2000
↑

JELGA
✦




CATEGORY	A	B	C	D
LPV DA	645-1 255 (300-1)			
LNAV/VNAV DA	707-1¼ 317 (400-1¼)			
LNAV MDA	920-1 530 (600-1)	920-1½ 530 (600-1½)	920-1¾ 530 (600-1¾)	
CIRCLING	920-1 530 (600-1)	1000-1¾ 610 (700-1¾)	1080-2¼ 690 (700-2¼)	

ELEV 390

D

TDZE 390



MIRL Rwy 13-31 **1**

MIRL Rwy 4-22 **1**

SC-1, 09 JUL 2026 to 06 AUG 2026

SC-1, 09 JUL 2026 to 06 AUG 2026