

WAAS CH 72812 W35A	APP CRS 354°	Rwy Ldg TDZE Apt Elev	6500 844 846
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35

MONROE COUNTY (BMG)

RNP APCH - GPS.

▼



▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Rwy 35 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using HUF altimeter setting. Circling Rwy 6, 24 NA at night. For inop ALS, increase LPV all Cats visibility to ¾ SM, LNAV Cats A/B visibility to 1 SM, and LNAV Cats C/D visibility to 1 ¾ SM. When local altimeter setting not received, use HUF altimeter setting: increase LPV DA to 1235 feet; increase LNAV/VNAV DA to 1485 feet and all visibilities ¾ SM; increase all MDAs 140 feet and LNAV visibility Cats C and D ¾ SM and Circling visibility Cats C and D ½ SM.

MALSRL

MISSED APPROACH: Climb to 3000 direct ITYEF and hold.

ASOS 134.525	HULMAN APP CON 128.025 339.8	BLOOMINGTON TOWER ★ 120.775 (CTAF)	GND CON 121.9	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------



3000 ITYEF				
4 NM Holding Pattern				
GP 3.00° TCH 50				
CATEGORY	A	B	C	D
LPV DA	1110-¾		266 (300-¾)	
LNAV/VNAV DA	1360-1		516 (600-1)	
LNAV MDA	1360-¾	516 (600-¾)	1360-1	516 (600-1)
CIRCLING	1380-1 534 (600-1)	1420-1 574 (600-1)	1420-1½ 574 (600-1½)	1620-2½ 774 (800-2½)