

WAAS
CH **56429**
W14A

APP CRS
135°

Rwy Ldg
TDZE **678**
Apt Elev **678**

RNAV (GPS) RWY 14


CHEROKEE COUNTY (J50)

▼
▲

Baro-VNAV NA when using Nacogdoches altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). When local altimeter setting not received, use Nacogdoches altimeter setting and increase all DA to 1046 feet and increase LPV visibility ½ SM and LNAV/VNAV visibility ¼ SM; increase all MDA 120 feet and LNAV visibility Cat C ¾ SM, Circling visibility Cat C ¼ SM. DME/DME RNP-0.3 NA. VDP NA with Nacogdoches altimeter setting.

MISSED APPROACH:
Climb to 3100 direct
NOPCI and hold.

AWOS-3PT 119.075	LONGVIEW APP CON* 128.75 379.15	UNICOM 122.7 (CTAF) 0
----------------------------	---	---------------------------------



4 NM Holding Pattern WOSUL		RUGKO 2200		RW14 678	
3100 ← 315° → 135° → 135°		2200		1.2 NM to RW14	
GP 3.00° TCH 30		6.1 NM		3.5 NM	
CATEGORY	A	B	C	D	
LPV DA	928-1	250 (300-1)		NA	
LNAV/VNAV DA	928-1	250 (300-1)		NA	
LNAV MDA	1080-1	402 (500-1)	1080-1 ½ 402 (500-1 ½)	NA	
CIRCLING	1080-1 402 (500-1)	1140-1 462 (500-1)	1280-1 ¾ 602 (700-1 ¾)	NA	