

ILS or LOC W RWY 16

LOC I-TYY

109.9

APCH CRS

164°

Rwy Idg

13,499

TDZE

1790

Arpt Elev

1799

[USAF]

DYESS AFB

(KDYS)

RADAR or DME required.

* When ALS inop, increase RVR to 40 and vis to ¾ mile.

** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CDE RVR to 60, vis to 1½ miles.

*** Circling to other than Rwy 34 not authorized.

ALSF-1

A1

1000

500

MISSED APPROACH: Climb to 4000 via DYS TACAN R-158 to HUGOE and hold.

ATIS ★

269.175

ABILENE APP CON

125.0 338.3 EAST

127.2 282.3 WEST

DYESS TOWER

133.0 257.675

GND CON

118.35 275.8

ASR

****When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1¾ miles.

DYS 29

2811

344°

164°

HOLD 10,000 5000

(IAF) HOGES DYS 20 5000

(IF) HIDUM DYS 15 2900

2047

344°

KAATE DYS 3.4

CENOT /RADAR DYS 5.1

Δ1934

3549

AVEME DYS 1.8

1985 2098 2006

LOCALIZER 109.9 I-TYY

HOLD 10,000 4000

2882

HUGOE DYS 15

2959

Δ2545

MSA DYS 2.5 NM

160°

270°

010°

3600

4600

4000

EMERG SAFE ALT 100 NM 4600

HOGES DYS 20

5000

164°

4300

CENOT RADAR DYS 5.1

2900

2440

KAATE DYS 3.4

DYS 2.5

AVEME DYS 1.8

4000 DYS R-158

HUGOE DYS 15

GS 2.60° TCH 48

1.6 NM

1.6 NM

0.6 NM

CATEGORY	A	B	C	D	E
S-ILS 16*	1990/24		200	(200-½)	
S-LOC 16**	2260/24	470 (500-½)	2260/50	470	(500-1)
CIRCLING***	2300-1 510 (600-1)	2320-1 530 (600-1)	2440-1¾ 650 (700-1¾)	2480-2¼ 690 (700-2¼)	2540-2¾ 750 (800-2¾)
KAATE FIX MINIMA					
S-LOC 16****	2200/24	410 (500-½)	2200/40	410	(500-¾)
CIRCLING***	2300-1 510 (600-1)	2320-1 530 (600-1)	2440-1¾ 650 (700-1¾)	2480-2¼ 690 (700-2¼)	2540-2¾ 750 (800-2¾)

ELEV 1799

TDZE 1790

A1

164°

91

ASSAULT STRIP

13,297 x 300

160°

164°

3488 x 60

345°

34

TWR

STAR

LIRL Rwy 164°-344°

HIRL Rwy 16-34

FAF to MAP 3.3 NM

Knots	60	90	120	150	180
Min:Sec	3:18	2:12	1:39	1:19	1:06

ABILENE, TEXAS

32°25'N-99°51'W

DYESS AFB (KDYS)

Amtd 4 19MAR26

ILS or LOC W RWY 16

SC-2, 06 AUG 2026 to 03 SEP 2026

SC-2, 06 AUG 2026 to 03 SEP 2026