


SE-2, 06 AUG 2026 to 03 SEP 2026

CHARLOTTE DEP CON
120.5 257.2
D-ATIS DEP
132.1
CLNC DEL
127.15 348.6
CPDLC
GND CON
121.8 348.6 (W)
121.9 348.6 (E)
CHARLOTTE TOWER
118.1 257.8 (18L-36R)
126.4 257.8 (1R-19L)
133.35 257.8 (1L-19R)

RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

NOTE: Turbojet only.
NOTE: If unable to accept climb rates, advise ATC on initial contact.
NOTE: Transponder code will be issued via PDC or Charlotte CLNC DEL.
NOTE: Accelerate to 250K, if unable advise ATC. Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.

TAKEOFF MINIMUMS
Rwys 1R, 18L, 19L/R, 36R: Standard with minimum climb of 500' /NM to 1260.
Rwy 1L: Standard with minimum climb of 500' /NM to 1400.



TOP ALTITUDE:
8000

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-2, 06 AUG 2026 to 03 SEP 2026