

CHICAGO, ILLINOIS

CHICAGO APP CON
128.2 353.875
GY D-ATIS
134.575
MDW D-ATIS
132.75

RNAV 1-DME/DME/IRU or GPS.
RADAR required.

ARRIVAL ROUTE DESCRIPTION

From PANGG on track 274° to cross MEGGZ at 11000, then on track 274° to cross AWSUM at 10000, then on track 273° to IROCK, then on track 273° to cross HALIE at 6000.

LANDING RUNWAY 4R: From HALIE on track 278° to cross OLCYK at or above 4000, then on track 278°. Expect RADAR vectors to final approach course.

LANDING RUNWAY 13L: From HALIE on track 279° to cross TINYLY at or above 4000, then on track 279°. Expect RADAR vectors to final approach course.

LANDING RUNWAY 22L: From HALIE on track 343° to cross GERMN at or above 4000, then on track 343° to LNANE, then on track 339° to BOCAH, then on track 274° to cross TACTT at 3000. Expect RNAV Rwy 22L approach or RADAR vectors to final approach course.

LANDING RUNWAY 31R: From HALIE on track 295° to cross ELIJO at 6000, then on track 295° to cross HILLS at 5000 and at 240K. Expect ILS or RNAV Rwy 31R approach or RADAR vectors to final approach course.

LANDING 05C/IGQ/3HO/GYY: From PANGG on track 274° to cross MEGGZ at 11000, then on track 274° to cross AWSUM at 10000, then on track 273° to cross HALIE at 6000, then on track 267° to cross JOSSH at 6000, then on track 267°. Expect RADAR vectors to final approach course.

LOST COMMUNICATIONS:
RUNWAY 22L: If approach clearance not received by TACTT, proceed inbound on RNAV (GPS) or RNAV (RNP) RWY 22L routing.

NOTE: Landing Rwy 31R: For non-RNP aircraft, expect RADAR vectors to final approach course.

MDW Ldg Rwy 22L
MDW Ldg Rwy 13L
MDW Ldg Rwy 31R
MDW Ldg Rwy 4R