CORPUS CHRISTI, TEXAS

TACAN Z RWY 13R

CORPUS CHRISTI NAS (TRUAX FLD) (KNGP)

[USN]

TACAN	APCH CRS	Rwy ldg	8001
NGP Chan 87	147°	TDZE	13
		Arpt Elev	18

* When ALS inop, increase CAT AB vis to 1 mile, CAT CD vis to 1⅛ miles.

SALSF

MISSED APPROACH: Climb to 1600 direct NGP TACAN and turn left to intercept R-041 to RYNOL and hold.

ATIS★	APP CON	NAVY CORPUS TOWER★	GND CON	ASR/PAR
127.9 290.9	120.9 259.3	134.85 L 340.2	118.7 257.85	

When local altimeter setting not received, use Corpus Christi (CRP) Intl altimeter setting.

IAF
CORPUS CHRISTI
115.5 CRP
Chan 102

544
554
549
616
154
1068
105
158
279
201

R-137
137°
1600
(IF)
YOMEN
NGP
10
147°
1600
LALEE
NGP
5.8
R-327
ACUXA
NGP
1.4
NGP
14
R-041
041°
230K
22°
HOLD 6000 1600
RYNOL
NGP
10

CAUTION:
Intermediate segment length 4.3 NM, less than
CAT AB 5.0 NM
CAT CD 6.0 NM

Northbound arrivals on V70-407 and V13-20-163 require turn in holding at CRP VORTAC (IAF) (See L-20), or RADAR vectors. Holding at CRP not authorized for TACAN users.

TRUAX
Chan 87 NGP

MSA NGP 25 NM
170°
2100
1600
360°

EMERG SAFE ALT 100 NM 11,100

† VDP not authorized when using Corpus Christi (CRP) Intl altimeter

1600 | NGP | NGP R-041

CRP VORTAC
YOMEN NGP 10
LALEE NGP 5.8
137° 147°
1600 1600 1600
NGP † 2
ACUXA NGP 1.4
NGP TACAN
2.99° TCH 45
4.4 NM 0.5

CATEGORY	A	B	C	D
S-13R *	400-¾ 387 (400-¾)		400-⅞ 387 (400-⅞)	
CIRCLING	460-1 442 (500-1)	480-1 462 (500-1)	520-1½ 502 (600-1½)	580-2 562 (600-2)
CORPUS CHRISTI (CRP) INTL ALTIMETER SETTING				
S-13R *	420-¾ 407 (500-¾)		420-1 407 (500-1)	
CIRCLING	500-1 482 (500-1)		540-1½ 522 (600-1½)	620-2 602 (700-2)

ELEV 18 | TDZE 13

147°
13R
8001 × 200
5001 × 96
5002 × 96
5002 × 136
13L
22
18
36
31L 31R
TWR

HIRL all rwys L
REIL Rwy 13L-31R L
REIL Rwy 4-22, 18-36, 31L

SC-3, 06 AUG 2026 to 03 SEP 2026
SC-3, 06 AUG 2026 to 03 SEP 2026