

WAAS CH 72602 W13A	APP CRS 131°	Rwy Ldg TDZE 922 Apt Elev 958
--	------------------------	---

RNAV (GPS) RWY 13

DES MOINES INTL (DSM)



⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.
For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4000 and LNAV Cats C and D visibility to RVR 4500.
RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct CYCLN and hold.

ATIS 119.55	DES MOINES APP CON 123.9 307.15	DES MOINES TOWER 118.3 257.8	GND CON 121.9 348.6
-----------------------	---	--	-------------------------------



	WATTY	CLIVE	TILTH	
	4 NM Holding Pattern		1.7 NM to RWY13	
	3500	2600		
	GP 3.00°			
	TCH 56			
	8.2 NM	3.4 NM	0.8 NM	0.9 NM
CATEGORY	A	B	C	D
LPV DA#	1122/24 200 (200-½)			
LNAV/VNAV DA	1172/24 250 (300-½)			
LNAV MDA	1240/24 318 (300-½)			
CIRCLING	1420-1	462 (500-1)	1600-1¾ 642 (700-1¾)	1760-2½ 802 (900-2½)