

WAAS
CH **42612**
W16A

APP CRS
164°

Rwy Ldg **7502**
TDZE **710**
Apt Elev **710**

RNAV (GPS) RWY 16

FORT WORTH MEACHAM INTL (FTW)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA.

⚠

** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

AS

MISSED APPROACH: Climb to 3000 direct PAXXE and hold.

ATIS 120.7	LONE STAR APP CON 118.1 306.95 (N) 135.975 379.9 (S)	MEACHAM TOWER 118.3 257.8	GND CON 121.9
----------------------	--	-------------------------------------	-------------------------

Procedure NA for arrivals on UKW VORTAC via V17-161 northbound.

Key features on the chart include:

- UKW VORTAC** at 3000 ft, 144° bearing, 3.5 NM distance.
- FOXEB IAF** at 3000 ft, 074° bearing, 5 NM distance.
- WORD IAF** at 2500 ft, 164° bearing, 6 NM distance.
- MESDE FAF** at 990 ft, 974 ft, 4 NM distance.
- RW16** at 3600 ft, 164° bearing, 1.5 NM distance.
- MISSED APCH FIX** at 3000 ft, 164° bearing, 4 NM distance.

ELEV 710

D

TDZE 710

164°

91

AS

4

7502 X 150

0.5% UP

35

34

HIRL Rwy 16-34

MIRL Rwy 17-35

4 NM Holding Pattern		WORD	MESDE	3000	PAXXE
3000		344°	164°	164°	
GP 3.00° TCH 57			2500		
		6 NM	3.9 NM	1.5 NM	
CATEGORY	A	B	C	D	
LPV DA **	910/24		200 (200-½)		
LNAV/VNAV DA	1284-1½		574 (600-1½)		
LNAV MDA	1240/24	530 (600-½)	1240/50 530 (600-1)	1240/60 530 (600-1¼)	
CIRCLING	1260-1 550 (600-1)	1280-1 570 (600-1)	1340-1¾ 630 (700-1¾)	1500-2½ 790 (800-2½)	

FORT WORTH, TEXAS

Amdt 1C 19MAY22

32°49'N-97°22'W

FORT WORTH MEACHAM INTL (FTW)

RNAV (GPS) RWY 16