

APP CRS
271°

Rwy Ldg
TDZE
3852

Apt Elev
3877

RNP AR APCH - GPS.

▼

▲

❄

Inop table does not apply to RNP 0.30 DA. For uncompensated Baro-VNAV systems, procedure NA below -28°C or above 54°C. For inop ALS, increase RNP 0.13 DA* visibility all Cats to ¾ SM, RNP 0.30 DA* visibility all Cats to 1¾ SM.

MALSR

AS

MISSED APPROACH: Climb to 12000 on the RNAV missed approach route to PIXXI and hold, continue climb-in-hold to 12000.

*Missed approach requires minimum climb of 280 feet per NM to 7800.

#Missed approach requires minimum climb of 375 feet per NM to 6300.

ATIS
120.4

HELENA APP CON *
119.5 229.4

HELENA TOWER *
118.3 (CTAF) 0 257.8

GND CON
121.9

UNICOM
122.95

Procedure NA for arrivals at HLN VORTAC on V113 northeast bound.

Procedure NA for arrivals at SUZZY on V343 westbound.

Procedure NA for arrival on HIA VOR/DME airway radials 353 CW 078.

MSA RW 27 25 NM

REIL Rlys 9, 17, and 35

MIRL Rlys 5-23 and 17-35

HIRL Rwy 9-27

ELEV 3877

D

TDZE 3852

12000

KISTY

tr 271°

tr 265°

KELTY

tr 275°

tr 275°

PIXXI

JEXUT

GOKME

See planview for multiple IF locations.

RW27

GP 3.00°

TCH 55

CATEGORY	A	B	C	D
RNP 0.13 DA*		4172-½	320 (300-½)	
RNP 0.20 DA#		4303-⅞	451 (500-⅞)	
RNP 0.30 DA#		4353-1	501 (500-1)	
RNP 0.30 DA		4866-4	1014 (1000-4)	

AUTHORIZATION REQUIRED

HELENA RGNL (HLN)

RNAV (RNP) Z RWY 27

NW-1, 06 AUG 2026 to 03 SEP 2026

NW-1, 06 AUG 2026 to 03 SEP 2026