

HI-ILS Z or LOC Z RWY 18

LOC I-OCZ 111.1	APCH CRS 177°	Rwy Idg 12,901 TDZE 1195 Arprt Elev 1219	[USAF]
---------------------------	-------------------------	---	--------

LINCOLN (KLNK)

DME, RADAR required for procedure entry.

* When ALS inop, increase RVR to 40, vis to ¾ mile.
 ** When ALS inop, increase vis to 1¾ miles.

ATIS 118.05 290.9	OMAHA APP CON 124.0 270.3	TOWER ★ 118.5 253.5	GND CON 121.9 275.8	CLNC DEL 120.7 225.4
-----------------------------	-------------------------------------	-------------------------------	-------------------------------	--------------------------------

*** When ALS inop, increase RVR to 45, vis to ¾ mile.
 † When ALS inop, increase vis to 2 miles.

When local altimeter setting not received use Beatrice altimeter.

LOCALIZER 111.1 I-OCZ

LINCOLN 116.1 LNK Chan 108

BEATRICE ALTIMETER SETTING

CATEGORY	C	D	E
S-ILS 18 *	1395/24	200	(200-½)
S-LOC 18 **	1820-1¾ 601 (700-1¾)	625	(700-1¾)
CIRCLING	1820-1¾ 601 (700-1¾)	1820-2 601 (700-2)	2040-3 821 (900-3)

BEATRICE ALTIMETER SETTING

S-ILS 18 ***	S-LOC 18 †
1486/24	1920-1½
291	725
(200-½)	(800-1½)

CIRCLING

1920-2 701 (800-2)	1920-2 ¼ 701 (800-2 ¼)	2140-3 ¼ 921 (1000-3 ¼)
-----------------------	---------------------------	----------------------------

FAF to MAP 4.9 NM					
Knots	120	140	160	180	200
Min:Sec	2:27	2:06	1:50	1:38	1:25

HI-ILS Z or LOC Z RWY 18