

ILS RWY 18 (SA CAT I & II)
DANE COUNTY RGNL/TRUAX FLD (MSN)

 Procedure NA when tower closed.
 SA CAT I: Requires specific OPSPEC, MSPEC, or LOA approval and use of HUD to DH.
 SA CAT II: Reduced lighting: Requires specific OPSPEC MSPEC, or LOA approval and use of autoland or HUD to touchdown.

MALSR

MISSED APPROACH: Climb to 2700 on MSN VORTAC R-180 to MONAH INT/MSN VORTAC 4.9 DME/RADAR and hold.

[illegible]

HIRL all Rwys **L**
REIL Rwys 3, 14 and 32 **L**

Amdt 2B 31OCT24

2700

↑ MSN R-180 MONAH INT

Use I-DSZ DME when on the localizer course.

RUKYI I-DSZ (6.6) RADAR

Remain within 10 NM

005°

2500

GATNE I-DSZ (9.8)

185°

2800

2700

2500

GS 3.00° TCH 57

10.94 5 NM 3.2 NM

CATEGORY	A	B	C	D
S-ILS 18	SA CAT I	RA 153/14	150 DA 1014	
S-ILS 18	SA CAT II	RA 103/12	100 DA 964	

SA CATEGORY I & II ILS SPECIAL AIRCREW
& AIRCRAFT CERTIFICATION REQUIRED

ILS RWY 18 (SA CAT I & II)