

|                                        |                        |                                                               |
|----------------------------------------|------------------------|---------------------------------------------------------------|
| WAAS<br>CH <b>42522</b><br><b>W18A</b> | APP CRS<br><b>185°</b> | Rwy Ldg <b>8606</b><br>TDZE <b>864</b><br>Apt Elev <b>887</b> |
|----------------------------------------|------------------------|---------------------------------------------------------------|

RNAV (GPS) RWY 18

DANE COUNTY RGNL/TRUAX FLD (MSN)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1 1/2 mile and LNAV Cat C/D visibility to 1 1/2 miles.  
\*\* RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH:  
Climb to 3000 direct  
DEKEY and hold.

|                             |                                         |                                               |                               |                         |
|-----------------------------|-----------------------------------------|-----------------------------------------------|-------------------------------|-------------------------|
| ATIS<br><b>124.65 278.3</b> | MADISON APP CON★<br><b>135.45 343.7</b> | MADISON TOWER★<br><b>119.3 (CTAF) 0 257.8</b> | GND CON<br><b>121.9 348.6</b> | UNICOM<br><b>122.95</b> |
|-----------------------------|-----------------------------------------|-----------------------------------------------|-------------------------------|-------------------------|

Procedure NA for arrivals at WREST on V177 northbound.

Procedure NA for arrivals at RANDO on V9-341 northeast bound.

Procedure NA for arrivals on DLL VORTAC airway radial 140.

MISSED APCH FIX  
DEKEY

MSA RW18 25 NM  
3600

|                 |          |                 |
|-----------------|----------|-----------------|
| ELEV <b>887</b> | <b>D</b> | TDZE <b>864</b> |
|-----------------|----------|-----------------|

HIRL all Rwy's 1  
REIL Rwy's 3, 14 and 32 1

|              |                            |                    |                            |                            |
|--------------|----------------------------|--------------------|----------------------------|----------------------------|
| 3000         | DEKEY                      | AYECO              | 4 NM Holding Pattern       |                            |
| *LNAV only   | *1.4 NM to RW18            | RUKIY 2500         | GATNE                      |                            |
| RW18         | 1.4                        | 3.6 NM             | 3.2 NM                     |                            |
| 2500         | 2700                       | 185°               | 005°                       |                            |
| 185°         | 185°                       | 3000               | GP 3.00° TCH 57            |                            |
| 1.4          | 3.6 NM                     | 3.2 NM             | 3.7 NM                     |                            |
| CATEGORY     | A                          | B                  | C                          | D                          |
| LPV DA **    | 1064/24 200 (200-1/2)      |                    |                            |                            |
| LNAV/VNAV DA | 1360-1 1/4 496 (500-1 1/4) |                    |                            |                            |
| LNAV MDA     | 1360/24                    | 496 (500-1/2)      | 1360/55                    | 496 (500-1)                |
| CIRCLING     | 1420-1 533 (600-1)         | 1460-1 573 (600-1) | 1460-1 1/2 573 (600-1 1/2) | 1700-2 3/4 813 (900-2 3/4) |

MADISON, WISCONSIN  
Amdt 2F 07DEC17

43°08'N-89°20'W

DANE COUNTY RGNL/TRUAX FLD (MSN)

RNAV (GPS) RWY 18

EC-3, 06 AUG 2026 to 03 SEP 2026

EC-3, 06 AUG 2026 to 03 SEP 2026