

WAAS CH 42910 W06A	APP CRS 063°	Rwy Ldg TDZE 156 Apt Elev 164	5001
--	------------------------	---	-------------

RNAV (GPS) RWY 6

HUDSON VALLEY RGNL (POU)

⚠

Circling NA to Rwy 7 and 25. Baro-VNAV NA when using Montgomery altimeter setting.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 49°C (120°F). Circling Rwy 15, 33 NA at night. Rwy 6 helicopter visibility reduction below ¾ SM NA. Rwy 15, 33 helicopter visibility reduction below 1 SM NA. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Montgomery altimeter setting: increase LPV DA to 574; increase LNAV/VNAV DA to 809 and all Cats visibility ¼ SM; increase all MDA 80 feet and LNAV Cats C/D and Circling Cats C/D visibility ¼ SM; inop table does not apply to LNAV Cats A/B; for inop ALS, increase LPV all Cats visibility to 1 ½ SM. For inop ALS when using Montgomery altimeter setting, increase LPV all Cats visibility to 1 ½ SM, LNAV/VNAV all Cats visibility to 2 SM and LNAV Cats C/D to 1 ½ SM.

MALSR

MISSED APPROACH:

Climb to 3000 direct JURIL and on track 061° to IGN VOR/DME and hold, continue climb-in-hold to 3000.

ATIS

126.75

NEW YORK APP CON

132.75 363.1

DUTCHESS COUNTY TOWER ★

124.0 (CTAF) 269.15

GND CON

121.8

UNICOM

122.95

4 NM Holding Pattern		3000 JURIL		tr 061°		IGN			
CANTY		WEXIR 2200		VIYUP 3 NM to RW06		RW06			
3200 ← 243°		063° →		063°		*1160			
GP 3.00°		TCH 58		6.2 NM		3.2 NM			
3 NM		3 NM		3 NM		3 NM			
CATEGORY	A	B	C	D					
LPV DA	503-1		347 (400-1)						
LNAV/VNAV DA	738-1 ½		582 (600-1 ½)						
LNAV MDA	740-1 584 (600-1)		740-1 ¼ 584 (600-1 ¼)						
CIRCLING	760-1 596 (600-1)		840-1 676 (700-1)		940-2 ¼ 776 (800-2 ¼)		1080-3 916 (1000-3)		

POUGHKEEPSIE, NEW YORK

Orig-F 30DEC21

41°38'N-73°53'W

HUDSON VALLEY RGNL (POU)

RNAV (GPS) RWY 6