

ILS Z or LOC Z RWY 14L

LOC I-TYF 111.5	APCH CRS 138°	Rwy Idg 10,008 TDZE 14 Arpt Elev 17	[USAF]
---------------------------	-------------------------	--	--------

TYNDALE AFB (KPM)

DME or RADAR required.

* When ALS inop, increase RVR to 40 and vis to ¾ mile.
 ** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile;
 CAT CDE vis to 1 ½ miles.

ATIS ★ 254.4	APP CON 125.2 392.1 (N abv 5000') 120.825 379.3 (N blw 5000') 124.15 338.35 (S abv 5000') 119.775 317.45 (S blw 5000')	TOWER ★ 133.95 263.15	GND CON 121.9 259.3	ASR/PAR
------------------------	--	---------------------------------	-------------------------------	---------

EMERG SAFE ALT 100 NM 3300

BUTOW PAM 15 4000 138° 1600 5.3 NM 0.5 NM	ARESS PAM 6.5 RADAR CUTMI PAM 1.2 NORWE PAM 3 NENCY PAM 15	3000 PAM R-140 138° 171° 10.188 x 200 10.188 x 150 TWR 32L 32R	Recommend Rwy 14L-32R for apch end engagement of A-Gear. HIRL all rwy
--	--	--	--

ELEV 17	TDZE 14
---------	---------

CATEGORY	A	B	C	D	E
S-ILS 14L *	214/24		200	(200-½)	
S-LOC 14L **	500/24	486 (500-½)	500/50	486	(500-1)
CIRCLING	540-1	523 (600-1)	540-1 ½ 523 (600-1 ½)	580-2	563 (600-2)

FAF to MAP 5.3 NM					
Knots	60	90	120	150	180
Min:Sec	5:18	3:32	2:39	2:07	1:46