

WAAS CH 78412 W26A	APP CRS 254°	Rwy Ldg TDZE 1487 Apt Elev 1497
--	------------------------	---

RNAV (GPS) RWY 26

EASTERN OREGON RGNL AT PENDLETON (PDT)

RNP APCH.

Circling Rwy 11 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500.
#RVR 1800 authorized with the use of FD or AP or HUD to DA.

MALSR

AS

MISSED APPROACH: Climb to 4300 direct CESMI and on track 261° to PDT VORTAC and hold, continue climb-in-hold to 4300.

ASOS 118.325	SPOKANE APP CON * 133.15 379.15	PENDLETON TOWER * 119.7 (CTAF) 257.8	GND CON 121.9 257.8	UNICOM 122.95
------------------------	---	--	-------------------------------	-------------------------

Procedure NA for arrivals at ALW VOR/DME on V536 northeast bound.

Procedure NA for arrivals at LACED on V4 southeast bound.

ELEV 1497	D	TDZE 1487
------------------	----------	------------------

REIL Rwy 11 and 29 **1**
MIRL Rwy 11-29 **1**
HIRL Rwy 8-26 **1**

3400 CESMI				PDT				VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 48).			
↑				ir 261°							
* LNAV only											
3400				SAYOS 2.5 NM to RW26				FAVUB 4300			
↑				* 1.1 NM to RW26				REYOT 4300			
1.1 NM				1.4 NM				6 NM			
2320*				254°				5600			
1.1 NM				1.4 NM				1.9 NM			
CATEGORY				A				B			
LPV				DA#				1687/24 200 (200-½)			
LNAV/VNAV				DA				1800/24 313 (400-½)			
LNAV MDA				1880/24 393 (400-½)				1880/40 393 (400-¾)			
CIRCLING				1920-1 423 (500-1)				1960-1 463 (500-1)			
								1980-1½ 483 (500-1½)			
								2200-2¼ 703 (800-2¼)			

PENDLETON, OREGON

EASTERN OREGON RGNL AT PENDLETON (PDT)

Orig-F 31DEC20

45°42'N-118°51'W

RNAV (GPS) RWY 26