

ILS Y or LOC Y RWY 1R

LOC I-MDG 109.9	APCH CRS 006°	Rwy Idg TDZE 217 Arprt Elev 233	[USAF]
RADAR or DME required			ALSIF-1
* When ALS inop, increase RVR to 40 and vis to ¾ mile. ** When ALS inop, increase RVR CAT AB to 55 and vis to 1 mile, RVR CAT CDE vis to 1½ miles.			MISSED APPROACH: Climb to 3000 on VAD TACAN R-007 to RANDA and hold.
ATIS ★ 142.6 273.5	VALDOSTA APP CON ★ 126.6 285.6	TOWER ★ 128.45 (CTAF) 257.625	GND CON 138.95 275.8

CAUTION: Remain west of VAD R-031 and VAD R-164 when R-3008 is active.

ELEV	233	TDZE	217
------	-----	------	-----

CATEGORY	A	B	C	D	E
S-ILS 1R*	417/24 200 (200-½)				
S-LOC 1R**	660/24 443 (500-½)		660/45 443 (500-⅔)		
CIRCLING	760-1 527 (600-1)		800-1½ 567 (600-1½)		800-2 567 (600-2)

FAF to MAP 4.3 NM					
Knots	60	90	120	150	180
Min:Sec	4:18	2:52	2:09	1:43	1:22