

WAAS CH 86405 W20A	APP CRS 204°	Rwy Ldg 8919 TDZE 270 Apt Elev 270
--	------------------------	---

RNAV (GPS) RWY 20
WESTFIELD-BARNES RGNL (BAF)

   -20°C	Baro-VNAV NA when using Bradley Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Bradley Intl altimeter setting and increase LPV DA to 561'; LNAV/VNAV DA to 996 and increase all Cats visibility to 2¼; all MDA 60 feet and LNAV Cats B, C, D and E visibility to 1¼. For inoperative MALSRR, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to 2½, LNAV Cat E visibility to 1½. Night landing: Rwy 15 NA.	MALSRR 	MISSED APPROACH: Climb to 1700 then climbing right turn to 4000 direct CTR VOR/RR and hold.
---	---	---	---

ATIS 127.1 263.15	BRADLEY APP CON 125.35 281.5	WESTFIELD TOWER ★ 125.075 (CTAF) 0 251.1	GND CON 121.7 289.4
------------------------------------	---	---	--------------------------------------

