

WAAS CH 86605 W30A	APP CRS 301°	Rwy Ldg TDZE Apt Elev	7704 405 410
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 30
TRI-CITIES (PSC)


RNP APCH - GPS.

Baro-VNAV and VDP NA when using HRI altimeter setting. Rwy 30 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C or above 54°C. When local altimeter setting not received, use HRI altimeter setting: increase LPV DA to 750 feet; increase LNAV/VNAV DA to 888 feet and all visibilities ¼ SM, and increase all MDAs 100 feet and LNAV and Circling visibility Cats C and D ¼ SM.

MALSF

MISSED APPROACH: Climb to 900 then climbing left turn to 5200 direct PAIDS and hold, continue climb-in-hold to 5200.

ATIS 125.65	SPOKANE APP CON ★ 128.75 377.2	TRI-CITIES TOWER ★ 135.3 (CTAF) 0 285.55	GND CON 121.8	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



ELEV 410 D TDZE 405

REIL Rwy 3L and 12L

MIRL Rwy 12-30

HIRL Rwy 3L-21R

900	5200	PAIDS	ACWEW	IHAYO	4 NM Holding Pattern
1.3 NM	1.6 NM	2.5 NM	6 NM		
1400	2200	10000	3300		
GP 3.00°	TCH 54				
CATEGORY	A	B	C	D	
LPV DA	655-¾	250 (300-¾)			
LNAV/VNAV DA	793-7/8	388 (400-7/8)			
LNAV MDA	880-¾	475 (500-¾)	880-1½	475 (500-1½)	
CIRCLING	900-1 490 (500-1)	940-1 530 (600-1)	1040-1¾ 630 (700-1¾)	1100-2¼ 690 (700-2¼)	

NW-1, 06 AUG 2026 to 03 SEP 2026

NW-1, 06 AUG 2026 to 03 SEP 2026