

APP CRS	Rwy Idg	5001
136°	TDZE	31
	Apt Elev	39

RNAV (GPS) RWY 13

TILLAMOOK (TMK)


▼

NA



DME/DME RNP-0.3 NA. When local altimeter setting not received, use Astoria Rgnl altimeter setting and increase all MDA 540 feet; increase LNAV Cat A visibility ¼ SM, Cat B visibility ½ SM, and Cat C visibility 1 SM and Circling Cat B visibility ¼ SM
Night Landing: Rwy 1, 19 NA. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climbing right turn to 5000 direct ULKAW and hold, continue climb-in-hold to 5000.

AWOS-3PT 120.0	SEATTLE CENTER 124.2 317.6	UNICOM 122.8 (CTAF) 0
-------------------	-------------------------------	--------------------------



ELEV 39	TDZE 31
---------	---------



Visual Segment - Obstacles.				5000	ULKAW
5 NM Holding Pattern					
FETUJ				INS AJ	QUCYO
4500				2800	
5.8 NM				6.5 NM	0.5
CATEGORY	A	B	C	D	
LNAV MDA	760-1	729 (800-1)	760-2 729 (800-2)	NA	
CIRCLING	880-1¼ 841 (900-1¼)	920-1¼ 881 (900-1¼)	1580-3 1541 (1600-3)	NA	