

WAAS CH 72810 W27A	APP CRS 274°	Rwy Ldg TDZE 770 Apt Elev 782
--	------------------------	---

RNAV (GPS) RWY 27

BISHOP INTL (F'NT)

▼



▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Rwy 27 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. For inop ALS, increase LNAV/VNAV all Cats visibility to 1¾ SM, LNAV Cat A/B visibility to 1 SM and LNAV Cat C/D visibility to 1¾ SM.

MALSR

MISSED APPROACH:
Climb to 3000 direct
CURGO and track
352° to CLIOO
and hold.

ATIS 133.15	GREAT LAKES APP CON ★ 118.8 257.9	FLINT TOWER ★ 126.3 (CTAF) 257.9	GND CON 121.9	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------



3000	CURGO	tr 352°	CLIOO	4 NM	JAGMI	Holding Pattern
* LNAV only			IYUPI 2.6 NM to RW27	274°	094°	2900
			*1.4 NM to RW27	*1640	274°	GP 3.00° TCH 56
				2400		
				2400		
				2.3 NM	6.1 NM	
CATEGORY	A	B	C	D		
LPV DA	1098-¾	328 (400-¾)				
LNAV/VNAV DA	1240-1	470 (500-1)				
LNAV MDA	1260-¾	490 (500-¾)	1260-1	490 (500-1)		
CIRCLING	1260-1 478 (500-1)	1300-1 518 (600-1)	1300-1½ 518 (600-1½)	1520-2¼ 738 (800-2¼)		