

HI-ILS Y or LOC Y RWY 26

LOC I-FSM
111.3

APCH CRS
260°

Rwy ldg
TDZE
Arpt Elev
9317
448
469

[USAF] FORT SMITH RGNL (EBBING FLD ANGB) (KFMSM)

DME required

▼ * When ALS inop, increase CAT E RVR to 40.
** When ALS inop, increase CAT CDE vis to 1½ miles.
▲ NA when control tower closed.




MALSR

MISSED APPROACH: Climb to 1400 then climbing left turn to 4000 on heading 224° and FSM VORTAC R-232 to SPIRO/FSM (1.5 DME) and hold. Continue climb in hold to 4000.


ATIS 124.775	RAZORBACK APP CON ★ 120.9 343.75	TOWER★ 118.3 (CTAF) 0 323.175	GND CON 121.9 275.8	CLNC DEL 133.85 278.3	ASR
------------------------	--	---	-------------------------------	---------------------------------	-----

*** Circling not authorized for CAT E NW of Rwy 8 and Rwy 20.
Circling not authorized for CAT E when R-2401B active.
Circling Rwy 20 and Rwy 26 not authorized at night.
RVR 1800 Authorized with use of FD or AP or HUD to DA.

Procedure not authorized for arrivals on
FSM VORTAC Airway Radials 359 CW 105.




EMERG SAFE ALT 100 NM 4500 FROM FSM VORTAC



CATEGORY	C	D	E
S-ILS 26 *	648/24	200	(200-½)
S-LOC 26 **	960-55	512	(600-1)
CIRCLING ***	1400-2¾ 931 (1000-2¾)	1400-3	931 (1000-3)

ELEV 469	TDZE 448
Rwy 02 ldg 5001'	618
Rwy 20 ldg 5001'	



HIRL Rwy 8-26	
MIRL Rwy 2-20	
FAF to MAP 7 NM	
Knots	120 140 160 180 200
Min:Sec	3:30 3:00 2:38 2:20 2:06

HI-ILS Y or LOC Y RWY 26