

LOC I-RGO	APP CRS	Rwy Ldg	7000
109.5	189°	TDZE	1218
		Apt Elev	1226


ILS or LOC RWY 19
AKRON-CANTON RGNL (CAK)

⚠ ** RVR 1800 authorized with the use of FD or AP or HUD to DA. For inoperative ALS, increase CAT C/D visibility to RVR 6000. ZEVLO fix minimums: For inoperative ALS, increase Cat C/D visibility to RVR 5500.


MALSR

MISSED APPROACH: Climb to 1700 then climbing left turn to 3000 direct BSV VOR/DME and hold.

ATIS 121.05	CLEVELAND APP CON★ 125.5 269.25	AKRON-CANTON TOWER 134.75 279.575	GND CON 121.7 348.6
----------------	------------------------------------	--------------------------------------	------------------------



ELEV 1226	D	TDZE 1218
-----------	---	-----------



	1700	3000	BSV	DERBY OM/INT BSV [15.4]	BUKIN INT BSV [22.4] RADAR
*LOC only			ZEVLO BSV [12.3]	2597	2800
			BSV [11.1]	*2600	*2700
				*1620	
				1.1	3.1 NM
					7 NM
CATEGORY	A	B	C	D	
S-ILS 19	**1418/24 200 (200-½)				
S-LOC 19	1620/24	402 (400-½)	1620/40	402 (400-¾)	
CIRCLING	1760-1	534 (600-1)	1780-1½ 554 (600-1½)	1800-2 574 (600-2)	
ZEVLO FIX MINIMUMS					
S-LOC 19	1580/24	362 (400-½)	1580/40 362 (400-¾)		
CIRCLING	1760-1	534 (600-1)	1780-1½ 554 (600-1½)	1800-2 574 (600-2)	