

ILS or LOC Z RWY 18

LOC I-EGI 111.7 **APCH CRS 184°** **Rwy Ldg TDZE 195** **Arprt Elev 195** **[USAF]** **DUKE FLD (EGLIN AF AUX NR 3) (KEGI)**

* When ALS inop, increase RVR to 40, vis to ¾ mile.
 ** When ALS inop, increase RVR to 55, vis to 1 mile.

ATIS ★ 244.575 **EGLIN APP CON 125.1 281.45 (271° - 089°) 132.1 360.6 (090° - 270°)** **TOWER ★ 133.2 290.425** **GND CON 123.25 251.125**

LOCALIZER 111.7 I-EGI

WARRINGTON Chan 2 DWG

EMERG SAFE ALT 100 NM 3500

TUSNE DWG 23 **TRAUT DWG 16.5 RADAR** **POOLR DWG 11.5**

800 **3000** **hdg 078°** **DWG R-033** **PAPPY DWG 23**

3000 **184°** **2000** **GS 3.00° TCH 59**

CATEGORY	A	B	C	D	E
S-ILS 18 *	395/24				
S-LOC 18 **	540/24	345 (400-½)	540/30	345 (400-¾)	
CIRCLING	680-1 485 (600-1)	740-1 545 (600-1)	740-1½ 545 (600-1½)	760-2 565 (600-2)	820-2¼ 625 (700-2¼)

FAF to MAP 5.0 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

HIRL Rwy 18-36 36

ASSAULT STRIP

TWR **346**

8025 x 150 **3500 x 60** **360°**