PENSACOLA, FLORIDA

RNAV (GPS) RWY 19

(USN)

PENSACOLA NAS (FORREST SHERMAN FLD) (KNPA)

APCH CRS 189°	Rwy ldg 7136 TDZE 22 Arpt Elev 28

RNP APCH - GPS

RADAR required

T

MISSED APPROACH: Climb to 800 then climbing right turn to 1500 direct FCTRY and hold.

ATIS	APP CON	SHERMAN TOWER	SHERMAN GND CON	ASR/PAR
124.35 266.8	120.65 270.8	120.7 340.2	121.7 336.4	

For uncompensated Baro-VNAV systems, Procedure NA below -15°C (5°F) or above 54°C (129°F).

HOLD 4000 1800 179° 230K 359° 4 NM

(IF/IAF) HEMDI

525

1600 177° (3.4)

429

WASIT

1500 (2)

PENSACOLA INTL

(FAF) HIKIB

211

189°

ROSCOE FLD

263

CITPI

223

100

RW19

MSA RW19 25 NM

3100

FCTRY

HOLD 11,000 1500

029° 230K 209°

4 NM

W155A

EMERG SAFE ALT 100 NM 3100

800 1500 FCTRY

HEMDI 359° 4000 1800

WASIT 177° 179°

1600

4 NM holding pattern

HIKIB 189°

1500

CITPI

700

RW19 1.2 NM to RW19

GP 3.00° TCH 55

2 NM 2.5 NM

ELEV 28 TDZE 22

189°

6 L

BCN TWR

19R 920 x 75 1L

25L 25R

8001 x 200

8002 x 200

A1 P

7L 7R

7136 x 200

1

210

HIRL Rwys 1-19, 7L-25R, and 7R-25L

REIL Rwys 1, 7L, 7R, 19, 25L, and 25R

CATEGORY	A	B	C	D	E
LNAV/VNAV DA	272-1 250 (300-1)		275-1 253 (300-1)	296-1 274 (300-1)	380-1 358 (400-1)
LNAV MDA	440-1 418 (500-1)		440-1⅛ 418 (500-1⅛)		
CIRCLING	520-1 492 (500-1)		540-1½ 512 (600-1½)	600-2 572 (600-2)	640-2¼ 612 (700-2¼)