JACKSONVILLE, ARKANSAS

ILS RWY 25 (CAT II)

LITTLE ROCK AFB [USAF] (KLRF)

LOC I-TYV	APCH CRS	Rwy ldg 12,001 TDZE 301 Arpt Elev 312
109.9	252°	

RNP APCH. RNAV1-GPS or RADAR required.

ALSF-2

MISSED APPROACH: Climb to 900 then climbing right turn to 3000 direct HERCK and hold.

ATIS ★	APP CON	TOWER	GND CON
119.175 251.1	119.5 306.2	120.6 269.075	132.8 275.8

CATEGORY II ILS-SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

ALTERNATE MISSED APPROACH: Climbing to 3000 fly runway heading until 2 DME, then turn right heading 360°, expect further clearance from ATC.

PROCEDURE EFFECTIVE BY NOTAM

4 NM HOLD 3000 162° 200K 342° HERCK

ATC RADAR required for holding above 4000′ or greater than 200 KIAS.

(IAF) AALII 230K — AALII entry NA for CAT E aircraft.

2000 NoPT (6) 162°

4 NM HOLD 4000 2000 072° 230K 252° 072°

JACKSONVILLE Chan 29 LRF (109.2)

294

1800 252° (4)

ATC RADAR required for holding above 4000′ or greater than 230 KIAS.

(IF/IAF) BIELD LRF 10 2000

HESUP RADAR LRF 6.1

R2403A

R2403B

CAT E Acft: RADAR required when R-2403 active

LOCALIZER 109.9 I-TYV

MSA RW25 25 NM 3200

ELEV 312 TDZE 301

EMERG SAFE ALT 100 NM 4000

900 3000 HERCK

BIELD LRF 10 4 NM Holding Pattern

072° 4000 2000

252° 2000

HESUP RADAR LRF 6.1

LRF TACAN

252° 1800

GS 3.00° TCH 56

993′ 4.6 NM

ASSAULT STRIP 071° 251° 0.4% UP 3361 x 60 12,001 x 150 07 25 TWR

CATEGORY	A	B	C	D	E
S-ILS 25	RA 94/12	100	DA 401		

HIRL Rwy 07-25
TDZL/RCLS Rwy 25

SC-1, 06 AUG 2026 to 03 SEP 2026

SC-1, 06 AUG 2026 to 03 SEP 2026