

TACAN RWY 25

TACAN LRF Chan 29	APCH CRS 259°	Rwy Idg 12,001 TDZE 301 Arpt Elev 312
-----------------------------	-------------------------	--

[USAF]

LITTLE ROCK AFB (KLRF)


* When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1½ miles.
** Circling not authorized S of Rwy 07-25. Circling not authorized to Assualt Strip.

ALSF-2


MISSED APPROACH: Climbing right turn to 3000 to intercept LRF R-342 outbound to HERCK and hold as published.

ALTERNATE MISSED APPROACH: Climbing to 3000, fly runway heading until LRF 2 DME, then turn right heading 360°, FFC from ATC


ATIS ★ 119.175 251.1	APP/DEP CON 119.5 306.2	TOWER 120.6 269.075	GND CON 132.8 275.8
-------------------------	----------------------------	------------------------	------------------------




ATC RADAR required
for holding above 4000'
or greater than 230 KIAS.



CAT E acft: RADAR required
when R-2403 active




EMERG SAFE ALT 100 NM 4000



CATEGORY	A	B	C	D	E
S-25 *	800/24 499 (500-½)		800/50 499 (500-1)		
CIRCLING**	800-1 488 (500-1)	880-1 568 (600-1)	880-1½ 568 (600-1½)	1040-2¼ 728 (800-2¼)	1040-2½ 728 (800-2½)

ELEV	312	TDZE	301
------	-----	------	-----



JACKSONVILLE, ARKANSAS

34°55'N-92°09'W

LITTLE ROCK AFB (KLRF)

Amdt 1 27NOV25

TACAN RWY 25

SC-1, 06 AUG 2026 to 03 SEP 2026