

WAAS
CH **61105**
W03A

APP CRS
030°

Rwy Ldg
TDZE **640**
Apt Elev **640**

RNAV (GPS) RWY 3

CHARLOTTESVILLE-ALBEMARLE (CHO)


RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C.
▲ When local altimeter setting not received, use Orange altimeter setting and increase LPV DA to 910, LNAV/VNAV DA to 985, and all MDA 80 feet; increase LNAV/VNAV all Cats visibility ½ SM, LNAV Cat C/D visibility ¼ SM and Circling Cats C/D visibility ¼ SM.
Baro-VNAV and VDP NA when using Orange altimeter setting. For Inop ALS, increase LNAV/VNAV all Cats visibility to ½ SM and LNAV Cats C/D visibility to 1 SM. For Inop ALS when using Orange altimeter setting, increase LPV all Cats visibility to ¾ SM, and LNAV/VNAV all Cats visibility to 1 SM.

MALSR

MISSED APPROACH:
Climb to 2000 then climbing right turn to 4000 direct GVE VORTAC and hold.

ATIS 118.425	POTOMAC APP CON 132.85 323.125	CHARLOTTESVILLE TOWER ★ 124.5 (CTAF) 0 338.275	GND CON 121.9 338.275	UNICOM 122.95
------------------------	--	--	---------------------------------	-------------------------



4 NM Holding Pattern

GP 3.00° TCH 54

WULDU	SIPME	JTTV	RW03
6000 ← 210°	2600	2.5 NM to RW03	
3400 → 030°	*1480	*1 NM to RW03	
	6.7 NM	3.5 NM	1.5 NM

ELEV 640	TDZE 640
2000	4000
GVE	
* LNAV only	

CATEGORY	A	B	C	D
LPV DA	840-½ 200 (200-½)			
LNAV/VNAV DA	915-½ 275 (300-½)			
LNAV MDA	1020-½ 380 (400-½)		1020-⅝ 380 (400-⅝)	
CIRCLING	1100-1 460 (500-1)		1500-2½ 860 (900-2½) 1500-2¾ 860 (900-2¾)	