

WAAS
CH **56209**
W01A

APP CRS
004°

Rwy Ldg **5992**
TDZE **140**
Apt Elev **141**

RNAV (GPS) RWY 1
WAYCROSS-WARE COUNTY (AYS)


▼

▲

DME/DME RNP-0.3 NA. When local alimeter setting not received, use Alma alimeter setting and increase LPV DA to 473 feet and all visibilities $\frac{1}{8}$ mile, LNAV/VNAV DA to 462 feet and all visibilities $\frac{1}{8}$ mile; increase all MDA 60 feet and visibility Cats C and D $\frac{1}{8}$ mile and Circling Cats C and D visibilities $\frac{1}{4}$ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Night Landing Rwy 5, 31 NA. VDP and Baro-VNAV NA when using Alma alimeter setting. Helicopter visibility reduction below $\frac{3}{4}$ SM NA.

MISSED APPROACH:
Climb to 1700 direct
BIJUV and hold.

AWOS-3 118.575	JACKSONVILLE CENTER 127.575 269.025	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



1700

↑

BIJUV

✦

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 33).

4 NM
Holding Pattern

AGMEQ

1800

BAQAV

*LNAV only.

RW01

2 NM

*2 NM to RW01

3.1 NM

5.9 NM

180°

180°

004°

004°

GP 3.00°

TCH 55

CATEGORY	A	B	C	D
LPV DA	423- ⁷ / ₈ 283 (300- ⁷ / ₈)			
LNAV/VNAV DA	412- ⁷ / ₈ 272 (300- ⁷ / ₈)			
LNAV MDA	820-1	680 (700-1)	820-1 ⁷ / ₈	680 (700-1 ⁷ / ₈)
CIRCLING	820-1	679 (700-1)	860-2 719 (800-2)	860-2 ¹ / ₄ 719 (800-2 ¹ / ₄)