

LOC I-FKL 110.5	APP CRS 207°	Rwy ldg TDZE 5200 Apt Elev 1540	ILS or LOC RWY 21 VENANGO RGNL (F'KL)
---------------------------	------------------------	---	--


RADAR required to define DACCA.
RADAR required for procedure entry.

For inop ALS, increase S-LOC 21 Cat C/D visibility to 1 SM.
Circling Rwy 12 NA at night.

MALSR
AS

MISSED APPROACH: Climb to 2200 then climbing right turn to 3400 direct FKL VOR and hold, continue climb-in-hold to 3400.

AWOS-3PT 118.175	YOUNGSTOWN APP CON ★ 126.25 322.3	CLNC DEL 126.25	UNICOM 122.7 (CTAF) 0
----------------------------	---	---------------------------	---------------------------------



ELEV 1540 TDZE 1540

207°

1596

3593 X 100

5200 X 150

3

MIRL Rwy 12-30

HIRL Rwy 3-21

FAF to MAP 5 NM

Knots

60 90 120 150 180

Min:Sec

5:00 3:20 2:30 2:00 1:40

2200 3400 FKL

AYUSU INT

3200

3400

207°

GS 3.00°

TCH 55

CATEGORY	A	B	C	D
S-ILS-21	1740-½ 200 (200-½)			
S-LOC-21	1900-½ 360 (400-½)		1900-⅝ 360 (400-⅝)	
CIRCLING	1960-1 420 (500-1)	2000-1 460 (500-1)	2040-1½ 500 (500-1½)	2100-2 560 (600-2)

FRANKLIN, PENNSYLVANIA
Amdt 6C 04NOV21

41°23'N-79°52'W

VENANGO RGNL (F'KL)
ILS or LOC RWY 21