

WAAS
CH **40301**
W35A

APP CRS
348°

Rwy Ldg **8002**
TDZE **21**
Apt Elev **24**

RNAV (GPS) RWY 35

ACADIANA RGNL (ARA)

RNP APCH - GPS.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C or above 54°C. Circling NA to Rwy's 17W and 35W. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cats C and D visibility to 1½ SM.

MALSR

AS

MISSED APPROACH: Climb to 440 then climbing right turn to 2000 direct LULEW and hold.

ASOS
133.325

LAFAYETTE APP CON★
121.1 268.7

ACADIANA TOWER★
125.0 (CTAF) 0 239.3

GND CON
121.7

UNICOM
122.95

MSA RW35 25 NM

2900

WOKDO

2.2 NM to RW35

(FAF) ISUCE

1700

348°

(8)

126

A

IF/IAF PLYI

168°

348°

4 NM

HOLD 6000 2000

2000 NoPT

072°

(6)

(IAF) HUBUM

2000 NoPT

307°

(14.8)

(IAF) ORICH

2000

073°

(23.9)

WHITE LAKE LLA

MISSED APCH FIX

LULEW

272°

092°

4 NM

440

2000

LULEW

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 52).

4 NM

Holding Pattern

ISUCE

1700

WOKDO

2.2 NM to RW35

1.2 NM to RW35

1700

348°

168°

6000

2000

760

1700

GP 3.00°

TCH 52

1.2 NM

1 NM

2.9 NM

8 NM

CATEGORY	A	B	C	D
LPV DA	221-½ 200 (200-½)			
LNAV/ VNAV DA	303-½ 282 (300-½)			
LNAV MDA	440-½	419 (500-½)	440-¾	419 (500-¾)
CIRCLING	440-1 416 (500-1)	480-1 456 (500-1)	600-1½ 576 (600-1½)	680-2 656 (700-2)

L1

8002 X 200

H

P

TWR

35

348°

HIRL Rwy 17-35

Seaway Rwy 17W-35W

NEW IBERIA, LOUISIANA

Amtd 1B 19MAR26

30°02'N-91°53'W

ACADIANA RGNL (ARA)

RNAV (GPS) RWY 35