

WAAS
CH **77909**
W27A

APP CRS
269°

Rwy Idg
TDZE
387
Apt Elev
387


RNAV (GPS) RWY 27
HENDERSON CITY-COUNTY (EHR)

RNP APCH.

Baro-VNAV NA when using Evansville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 27 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Evansville altimeter setting and increase all DA 41 feet and all MDA 60 feet and LPV all Cats, LNAV/VNAV all Cats and LNAV Cats C/D visibilities ¼ mile.

MISSED APPROACH: Climb to 2500 direct BIKME and hold.

AWOS-3PT 118.85	EVANSVILLE APP CON ★ 124.025 257.8	UNICOM 122.8 (CTAF) 0
---------------------------	--	--



ELEV 387

TDZE 387

REIL Rwy 9 and 27 **0**

MIRL Rwy 9-27 **0**

2500

BIKME

ONZIG

SIZBY

GOTVE

RW27

269°

270°

2500

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	733-1¼ 346 (400-1¼)			
LNAV/VNAV DA	827-1½ 440 (500-1½)			
LNAV MDA	840-1	453 (500-1)	840-1¾ 453 (500-1¾)	840-1½ 453 (500-1½)