



WAAS CH 58105 W19A	APP CRS 191°	Rwy Ldg 11500 TDZE 302 Apt Elev 312
--	------------------------	--

RNAV (GPS) Y RWY 19L
WASHINGTON DULLES INTL (IAD)

RNP APCH - GPS.		ALSF-2	MISSED APPROACH: Climb to 800 then climbing left turn to 3000 direct ASPER and hold.
Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -13°C or above 54°C. Use of FD or AP required during simultaneous operations. *RVR 1800 authorized with use of FD or AP or HUD to DA.			
D-ATIS 134.85	POTOMAC APP CON 120.45 306.925 (241°-330°) 128.525 306.925 (091°-240°) 126.1 338.25 (331°-090°)	DULLES TOWER 120.1 317.8 (Rwy 1R/19L) 120.25 348.6 (Rwy 1C/19C) 134.425 348.6 (Rwys 1L/19R and 12/30)	GND CON 121.9 317.8 (EAST) 121.625 348.6 (WEST)



800	3000	ASPER	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).			
		DOMSE	TOOPR	THRET	FORKL	LEMIU
1.2 NM 1500		LOOOT	LEFFY	5000	6000	7000
1.2		2.4	2.5 NM	3.2 NM	3.3 NM	3.1 NM
CATEGORY		A	B	C	D	
LPV DA*		502/24 200 (200-½)				
LNAV/VNAV DA		760/45 458 (500-¾)				
LNAV MDA		760/24 458 (500-½)	760/45 458 (500-¾)			
CIRCLING		940-1 628 (700-1)	940-1¾ 628 (700-1¾)		1180-2¾ 868 (900-2¾)	