

WAAS CH 86537 W11A	APP CRS 116°	Rwy Ldg TDZE Apt Elev	6501 718 722
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 11
COLES COUNTY MEML (MTO)

RNP APCH.

A When local altimeter setting not received, use Champaign/Urbana altimeter setting and increase all DA 82 feet, increase all MDA 100 feet, and increase LPV all Cats visibility $\frac{1}{8}$ mile, LNAV/VNAV all Cats visibility $\frac{3}{8}$ mile, LNAV Cats C and D and Circling Cat C visibility $\frac{1}{4}$ mile, and Circling D visibility $\frac{1}{2}$ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Baro-VNAV and VDP NA when using Champaign/Urbana altimeter setting. Circling NA to Rwy 18 and 36.

MISSED APPROACH:
Climb to 1200 then
climbing left turn to
3000 direct NIBIE
and hold.

ASOS 118,475	CHAMPAIGN APP CON ★ 132.85 290.225	UNICOM 122.7 (CTAF) 0
------------------------	--	---------------------------------



4 NM
Holding Pattern

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 26).

1200 ↑
3000 ↘
NIBIE ✦

* LNAV only.

WUBTA
YAYSU
ZOSIB
RW11

3000 ← 296°
← 116° → 116°
2400
1680*

GP 3.00°
TCH 45

6 NM 2.3 NM 1.8 NM 1.1 NM

CATEGORY	A	B	C	D
LPV DA	918-¾ 200 (200-¾)			
LNAV/VNAV DA	1175-1½ 457 (500-1½)			
LNAV MDA	1120-1 402 (400-1)		1120-1½ 402 (400-1½)	
CIRCLING	1160-1 438 (500-1)	1180-1 458 (500-1)	1240-1½ 518 (600-1½)	1380-2 658 (700-2)

MIRL Rwy 6-24
HILL Rwy 11-29
REIL Rws 6, 11, and 24

MATTOON/CHARLESTON, ILLINOIS
Orig-B 16AUG18

39°29'N-88°17'W

COLES COUNTY MEML (MTO)
RNAV (GPS) RWY 11

EC-3, 06 AUG 2026 to 03 SEP 2026